

### Features

- Flush is activated by a no-touch sensor mounted inside the tank.
- Powered by 4 AA batteries (included).
- 1.28 gallons per flush (gpf).
- When batteries are low, the unit will beep five times at half-second intervals when activated to indicate it's time to replace them.
- Combines with the K-4309 bowl to create a complete K-6418 Cimarron toilet.
- Coordinates with other products in the Cimarron collection.
- Touchless has no impact on water usage.

### Technology

- Touchless module projects a field through the top of the tank lid that senses your hand, causing the toilet to flush.
- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl, and trapway to create a strong siphon during flushing.
- AquaPiston canister allows water to flow into the bowl from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3-inch flapper, for leak-free performance.
- Light-touch canister flush requires a lower actuation force than a flapper.

### Recommended Accessories

K-4309 Elongated Toilet Bowl



### Codes/Standards








ASME A112.19.2/CSA B45.1

### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

| Color  | Code | Description  |
|--|------|--------------|
|  | 0    | White        |
|  | 96   | Biscuit      |
|  | 47   | Almond       |
|  | NY   | Dune         |
|  | 95   | Ice™ Grey    |
|  | G9   | Sandbar      |
|  | 7    | Black Black™ |

No image available.

This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Toilet type: Two-piece

### Notes

Install this product according to the installation instructions.