



# “Rip Stop” Silver Jacket



## Product Specifications

Quietflex manufactures flexible duct for the commercial, residential and manufactured home industries. We produce 3" through 22" duct in R4.2 and R6.0 and 3" through 20" duct in R8.0.

The Quietflex “Rip Stop” Silver Jacket Flex Duct has a metallic, polyester-vapor barrier with a special “rip stop” scrim reinforcement.

[www.quietflex.com](http://www.quietflex.com)

## Key Features & Benefits

- Johns Manville Formaldehyde-free™ fiber glass insulation
- GREENGUARD® certified insulated products
- Galvanized or bronze metal core reinforcing
- Oversized core to fit on collars and register boxes
- Weather-resistant packaging
- Easy-to-carry package: Up to 10" bags are strapped to form a pair
- Available in boxes and bags
- 12.5', 25', 50' and custom lengths available
- HUD /FHA standards 515.2.1, paragraph B
- NFPA standards 90A and 90B
- Meets most BOCA, City of Chicago, federal, state and local codes and standards
- UL listed/approved to UL 181

## Other products we offer:

- Air Handling - Duct Board
- Air Handling - Duct Wrap



HARDI



QUALITY MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
ISO 9001:2000



# FLEX DUCT PRODUCT:

RIP STOP SILVER JACKET – FLEXIBLE DUCT

### Configurations

- Diameters available: 3-22" R4.2 and R6.0, 3-20" R8.0
- Lengths available: 12.5', 25' and 50' and custom lengths available

### Approvals

- UL Classified/Approved to UL 181 Standard
- NFPA standards 90A and 90B
- HUD/FHA standards 515.2.1 Paragraph B
- Meets most federal, state and local codes and standards
- GREENGUARD certified entire sleeve construction

### Fiberglass

- R4.2, R6.0 and R8.0 certified by UL and the Air Diffusion Council using ASTM C-518 at installed thickness of insulation
- Made of formaldehyde free materials

### Surface burning characteristics

- Flame spread: Less than 25
- Smoke developed: Less than 50

### Vapor barrier

- The Quietflex Rip Stop Silver Jacket has a metalized polyester-vapor barrier with a special "rip stop" scrim reinforcement
- Vapor Transmission: at or below 0.05 perms



### Operating temperature range

- -20°F to 180°F - Continuous
- -20°F to 200°F - Intermittent

### Core

- Two layers of polyester film encapsulate a galvanized or bronze coated wire helix
- Rated positive pressure is 10" W.C. and negative pressure is 1/2" W.C. per the UL 181 standard
- Rated maximum air velocity is 6000 FPM

<b>Job Name</b>		<b>Submitter:</b>		<b>Date:</b>	
<b>Location</b>					Metalized polyester vapor barrier/silver jacket sleeve
<b>Contractor</b>					
<b>Engineer</b>					
<b>Architect</b>					
					<b>QFSD-006-01</b>

4518 Brittmoore Road • Houston, Texas 77041 • Phone 713.849.2163 • quietflex.com

#### Limited Warranty | Limitation of Liability | Disclaimer of Unstated Warranties

The flexible air duct is warranted by Quietflex Manufacturing Company, L.P., for ten (10) years against defects in material and workmanship. This warranty is for exchange of duct only and does not include installation.

#### Warranty Exclusions

Warranty is excluded if flexible air duct is used in the following installations / applications:  
 1. Where duct is exposed to direct or indirect light.  
 2. Where duct is used on the high – pressure side of variable air – volume (VAV) systems.

#### Limitation of Liability

Quietflex's liability for damages, whether in contract, in tort, under warranty, in negligence or otherwise, shall not exceed the return of the amount of the purchase price paid for the Quietflex products. Quietflex shall not be liable for special, indirect or consequential damages. Specification and performance data listed herein are subject to change without notice.

#### Disclaimer of Unstated Warranties

This warranty is the only warranty of Quietflex products. All other warranties, expressed or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose are expressly disclaimed. Quietflex is a registered trademark of Quietflex Manufacturing Company, L.P.